



Product Specifications

Model Number	MAX. PRESS.		MAX. SPEED	HP	kW	Net Wt.	
	bar.	PSI				lbs.	kg
2AM-FCC-1	7.0	100	3,000 RPM	.95	0.70	4.4	2.0
2AM-FCC-1B	7.0	100	3,000 RPM	.95	0.70	4.4	2.0
2AM-FCW-13	7.0	100	3,000 RPM	.95	0.70	4.4	2.0
* 2AM-FCW-13B	7.0	100	3,000 RPM	.95	0.70	4.4	2.0

SOUND LEVEL 76 dB(A) MAX.

NORMAL AMBIENT +1°C. - 120°C.

RELATIVE HUMIDITY 0% - 100%

ENVIRONMENT HAZARDOUS AMBIENT COMBUSTIBLE GAS AND DUST +1°C TO +40°C

CONFORMS TO EUROPEAN STD. EN13463-1 NON-ELECTRICAL EQUIPMENT FOR EXPLOSIVE ATMOSPHERES GROUP II, CAT. 2 (GAS & DUST) PROTECTED BY CONSTRUCTION (SURFACE TEMP. RATING 135°C)

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE FOR REFERENCE ONLY UNLESS OTHERWISE TOLERANCED.

* DENOTES INACTIVE

